

PLICORD FUEL DISCHARGE



Product Specification

Application

Plicord® Fuel Discharge hose is for the discharge of gasoline, oil, ethanol blends and other petroleum based products in tank and industrial applications.

Construction Tube

Nitrile synthetic rubber RMA Class A (High Oil Resistance), plus antistatic wires

Cover

Black Chemivic™ synthetic rubber RMA Class B (Medium-High Oil Resistance)

Reinforcement

Spiral-plied synthetic fabric (2"-4": 2 ply 6": 4 ply), plus grounding wires

Temperature Range

-35 to 180

Packaging

100' lengths, coiled and polywrapped

Branding Spiral

Example: ContiTech Plicord® Fuel Discharge

Coupling

Use ContiTech Insta-Lock Cam & Groove Fittings with this product. See the Coupling Systems information pages at the back of the catalog.

Non Stock / Sizes

For special production run minimum requirements, see Appendix D.

Order Codes

543-331

PLICORD FUEL DISCHARGE

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	PSI	MPa	lb./ft.	kg./m.
3/4	19.1	1.21	30.7	150	1.03	0.42	0.63
1	25.4	1.46	37.1	150	1.03	0.52	0.77
1¼	31.8	1.72	43.7	150	1.03	0.63	0.94
1½	38.1	1.95	49.5	150	1.03	0.73	1.09
2	50.8	2.49	63.3	150	1.03	0.98	1.46
2½	63.5	2.98	75.7	150	1.03	1.19	1.77
3	76.2	3.5	88.9	150	1.03	1.45	2.16
3 1/2	88.9	4.04	102.6	150	1.03	1.7	2.53
4	101.6	4.52	114.8	150	1.03	1.91	2.84
6	152.4	6.63	168.4	150	1.03	3.41	5.07
8	203	8.80	223.6	150	1.03	6.13	9.12